

14 Plafo>The LED Plafo Range

62026D/W/W



50W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads






Dimensions




Physical Specification

| | |
|-------------------|---------------------|
| Item Group | 14 Plafo |
| Family | The LED Plafo Range |
| Order Code | 62026D/W/W |
| Colour | White |
| Material | Metal |
| Diffuser Material | Plastic |
| Shape | Circular |
| Height | 75mm |
| Diameter | 535mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |

| Gear | Built In |
|------------------|---|
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 50W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 430mA |
| Voltage | 106,9V |
| Power(Watts) | 45,96 |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Sanan |
| F Mark |  |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 38,7-56W |

| | |
|------------------|---|
| Power Factor | 0,9 |
| Constant Current | Yes |
| Output | 430mA |
| Voltage Range | 90-130V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 3750lm |
| Light Efficiency | 75lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Length | 55cm |
| Box Width | 55cm |
| Box Height | 7,8cm |
| Box Weight | 2.240kg |
| Pcs/Carton | 5 |
| Barcode | 5291889069232 |
| HS Code | 9405413990 |

Certification & Warranty

switch to
one light!

one
LIGHT

