

06 Downlights Fixed LED>The COB Project Round Range

10105K/G/W



5W COB LED project round range downlight, IP53.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification

| | |
|------------|-----------------------------|
| Item Group | 06 Downlights Fixed LED |
| Family | The COB Project Round Range |
| Order Code | 10105K/G/W |
| Colour | Grey |
| Material | Die Cast |
| Shape | Circular |
| Height | 100mm |

| | |
|----------------------|-------|
| Diameter | 123mm |
| Cutout Hole Diameter | 107mm |
| Recessed Ceiling | Yes |
| Depth Required | 130mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics

| Gear | External-Included |
|------------------|---|
| Fitting + Driver | |
| Input Voltage | 100-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 5W |
| IP Rating | IP53 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

| Fitting | |
|---------------|---|
| Input Type | Constant Current |
| Input Current | 400mA |
| Voltage | 10,5V |
| Safety Class |  |
| Power(Watts) | 4,2W |
| IP Rating | IP53 |
| Light Source | LED built in |
| LED Brand | GH |

Gear

Gear Type

Led Driver

Input Voltage

100-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

3-7W

Power Factor

0,8

Constant Current

Yes

400mA

6-14V

IP Rating

IP20

Safety Class



Dimmable

No

Ambient Temp

40°C

Operating Temp

80°C

Housing Material

Plastic

Output Terminal

Cable

Illumination Data

Colour Temperature

3000K

Lumen Output

350lm

Light Efficiency

70lm/W

CRI

80

Beam Angle

100°

Illumination Diagram



Packing Info

Box Length

13,5cm

Box Width

13cm

| | |
|------------|---------------|
| Box Height | 11,5cm |
| Box Weight | 0,450kg |
| Pcs/Carton | 24 |
| Barcode | 5291889028109 |
| HS Code | 9405409900 |

Certification & Warranty

| | |
|----------------|---------|
| Warranty | 2 Years |
| Weee Directive | Yes |

switch to
one light!

one
LIGHT

