



# **Product Datasheet**

### 06 Downlights Fixed LED>The IP54 Bathroom Downlights

# 10107B/W/C



7W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED 180mA driver.

Complies with standard EN60598-1 and any other specific standards.











### Downloads










#### Dimensions



80mm



45mm

#### Gallery







#### **Physical Specification**

Item Group Family Order Code Colour Material **Diffuser Material** Shape

06 Downlights Fixed LED

The IP54 Bathroom Downlights

10107B/W/C

White

Die Cast

Plastic

Circular

Height	45mm
Diameter	80mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	180mA
Voltage	35V
Safety Class	<u> </u>
Power(Watts)	6,3W
IP Rating	IP54
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	14
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	5,4-7,2W
Power Factor	0,9
Constant Current	Yes
Output	180mA
Voltage Range	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Cable
Brand	0
Protection	Short Circuit and Overload
llumination Data	
Colour Temperature	4000K
Lumen Output	540lm
Light Efficiency	77,14lm/W
CRI	80
Beam Angle	90°



## Packing Info

Box Length	10cm
Box Width	10cm
Box Height	9cm
Box Weight	0.228kg
Pcs/Carton	50
Barcode	5291889043195
HS Code	9405413990

#### Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes



