

Product Datasheet

www.1-light.eu

02 Recessed Spots Fixed LED>The Fire Rated IP65 Range

10107DF/W



7W COB LED Fire Rated 90 minutes recessed Spot, IP65.

Supplied with Triac dimmable LED driver.

Complete with white ring.

Complies with standard EN60598-1 and any other specific standards.















Downloads










Dimensions



Gallery



Related items







050178/C

Physical Specification

Item Group

02 Recessed Spots Fixed LED

Family

The Fire Rated IP65 Range

Order Code	10107DF/W
Colour	White
Material	Metal
Shape	Circular
Height	65mm
Diameter	78mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Fitting + Driver	
Input Voltage	220-240V
Input Voltage 50 Hz	Yes
Input Voltage 50 Hz 60 Hz	
Input Voltage 50 Hz 60 Hz Safety Class	Yes Yes
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts)	Yes Yes 7W
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating	Yes Yes TW IP65
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source	Yes Yes TW IP65 LED built in
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	Yes Yes TW IP65 LED built in Yes
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type	Yes Yes Triac
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable	Yes Yes TW IP65 LED built in Yes
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type F Mark	Yes Yes Triac
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type	Yes Yes Triac
Input Voltage 50 Hz 60 Hz Safety Class Power(Watts) IP Rating Light Source Dimmable Dimmer type F Mark	Yes Yes Triac

IP Rating	IP65
Light Source	LED built in
LED Type	SMD
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Safety Class	
Output Terminal	Connector
Illumination Data	
Colour Temperature	3000K
Lumen Output	500lm
Light Efficiency	
	71,42lm/W
CRI	71,42lm/W 80
CRI Beam Angle	
	80
Beam Angle	80 60°
Beam Angle Illumination Diagram	80 60°
Beam Angle Illumination Diagram	80 60°
Beam Angle Illumination Diagram	80 60°
Beam Angle Illumination Diagram Packing Info	80 60°
Beam Angle Illumination Diagram Packing Info Box Weight	80 60°

Certification & Warranty

switch to one light!

