



Product Datasheet

New 2025 Edition 2>Downlights Fixed LED

10118B/W/V



18W LED CCT Variable recessed downlight, IP54. Suitable for bathroom installations.

Complete with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.














Downloads







Dimensions



170mm



45mm

Gallery







Physical Specification

Item Group	
Family	
Order Code	
Colour	
Material	
Diffuser Material	
Shape	

New 2025 Edition 2

Downlights Fixed LED

10118B/W/V

White

Die Cast

Plastic

Circular

Height	45mm
Diameter	170mm
Cutout Hole Diameter	140mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	18W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	450mA
Safety Class	
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
Output	450mA
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	0
lumination Data	
Colour Temperature	3000K-4000K-5000K
Colour Temperature Lumen Output	3000K-4000K-5000K 1400lm
Lumen Output	1400lm
Lumen Output Light Efficiency	1400lm 77lm/W
Lumen Output Light Efficiency CRI	1400lm 77lm/W 80
Lumen Output Light Efficiency CRI Beam Angle	1400lm 77lm/W 80 90°
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1400lm 77lm/W 80 90°
Lumen Output Light Efficiency CRI Beam Angle	1400lm 77lm/W 80 90°
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1400lm 77lm/W 80 90°
Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram acking Info	1400lm 77lm/W 80 90°

Certification & Warranty

switch to one light!

