



05 Downlights Fixed>The IP54 & IP65 Downlights CCT V

10130BX/B/V



30W CCT Variable SMD recessed downlight.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery



Physical Specification

|            |                                  |
|------------|----------------------------------|
| Item Group | 05 Downlights Fixed              |
| Family     | The IP54 & IP65 Downlights CCT V |
| Order Code | 10130BX/B/V                      |
| Colour     | Black                            |
| Material   | Aluminium                        |
| Shape      | Circular                         |
| Height     | 55mm                             |

|                      |       |
|----------------------|-------|
| Diameter             | 225mm |
| Cutout Hole Diameter | 205mm |
| Recessed Ceiling     | Yes   |
| Depth Required       | 80mm  |
| Indoor               | Yes   |
| Outdoor              | Yes   |
| Adjustable           | No    |

Electrical Characteristics

|                  |                                                                                       |
|------------------|---------------------------------------------------------------------------------------|
| Gear             | External-Included                                                                     |
| Fitting + Driver |                                                                                       |
| Input Voltage    | 220-240V                                                                              |
| 50 Hz            | Yes                                                                                   |
| 60 Hz            | Yes                                                                                   |
| Safety Class     |  |
| Power(Watts)     | 30W                                                                                   |
| IP Rating        | IP65                                                                                  |
| Light Source     | LED built in                                                                          |
| F Mark           |  |

|               |                  |
|---------------|------------------|
| Fitting       |                  |
| Input Type    | Constant Current |
| Input Current | 700mA            |
| Light Source  | LED built in     |
| LED Type      | SMD              |

|               |            |
|---------------|------------|
| Gear          |            |
| Gear Type     | Led Driver |
| Input Voltage | 220-240V   |
| 50 Hz         | Yes        |

|        |       |
|--------|-------|
| 60 Hz  | Yes   |
| Output | 700mA |

| Illumination Data    |                                                                                     |
|----------------------|-------------------------------------------------------------------------------------|
| Colour Temperature   | 3000K-4000K-5000K                                                                   |
| Lumen Output         | 2700lm                                                                              |
| Light Efficiency     | 90lm/W                                                                              |
| CRI                  | 90                                                                                  |
| Beam Angle           | 90                                                                                  |
| Illumination Diagram |  |

| Packing Info |         |
|--------------|---------|
| Box Weight   | 1.150kg |
| Pcs/Carton   | 10      |

| Certification & Warranty |         |
|--------------------------|---------|
| Warranty                 | 5 years |
| Weee Directive           | Yes     |

switch to  
one light!

