



13 Wall & Ceiling LED>The Dark Light Ceiling Lights

12110H/B/W



10W Dark light surface ceiling spot, IP20.

Complete with 700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Dark Light Ceiling Lights
Order Code	12110H/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	83mm
Diameter	72mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	12V
Safety Class	
Power(Watts)	8,4W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3535
LED Brand	Bridgelux
LED Number	4
F Mark	

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	7,7-11,9W
Power Factor	0,85
Constant Current	Yes
700mA	11-17V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C...+45°C
Operating Temp	75°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	700lm
Light Efficiency	70lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.306kg
Pcs/Carton	30
Barcode	5291889074687
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

