



13 Wall & Ceiling LED>Zoomable Moving Heads COB

12115G/W/W



15W COB LED zoomable 15°-45° adjustable ceiling light with removable honeycomb.

Supplied with 350mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Zoomable Moving Heads COB
Order Code	12115G/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	95mm
Diameter	80mm
Recessed Ceiling	Yes
Indoor	Yes
Adjustable	2 Directions

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	41V
Safety Class	
Power(Watts)	14,35W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	10,5-14,7W
Power Factor	0,9
Constant Current	Yes
350mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KGP
Protection	Short Circuit Protection,Overload Protection,No-load Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1500lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	15°-45°
Illumination Diagram	

Packing Info

Box Weight	0.485kg
Pcs/Carton	40
Barcode	5291889076384
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

