

13 Wall & Ceiling LED>The Dark Light Mirror Cylinders

12120X/W/W



20W Surface ceiling spot, IP20.

Complete with 450mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Dark Light Mirror Cylinders
Order Code	12120X/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	58mm
Diameter	116mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting	
Input Type	Constant Current
Input Current	450mA
Voltage	36V
Safety Class	
Power(Watts)	16,2W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Sanan
LED Number	12
F Mark	

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	12,15-18W
Power Factor	0,9
Constant Current	Yes
450mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C...+60°C
Operating Temp	85°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1600lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.603kg
Pcs/Carton	30
Barcode	5291889074496
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

