

13 Wall & Ceiling LED>The Dark Light Mirror Cylinders

12124X/W/W



24W Surface ceiling spot, IP20.

Complete with 600mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Dark Light Mirror Cylinders
Order Code	12124X/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	58mm
Diameter	160mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	36V
Safety Class	
Power(Watts)	21,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Sanan
LED Number	18
F Mark	

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	16,8-25,2W
Power Factor	0,9
Constant Current	Yes
600mA	28-42
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C...+60°C
Operating Temp	85°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1900lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.960kg
Pcs/Carton	20
Barcode	5291889074502
HS Code	9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

