



Product Datasheet

New 2025 Edition 3>Industrial & Floodlights

38120M/V



25W LED CCT Variable & Power variable industrial fitting. Stainless steel clips included. Polycarbonate body and diffuser.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Gallery





Physical Specification

Item Group	New 2025 Edition 3
Family	Industrial & Floodlights
Order Code	38120M/V
Colour	Grey
Material	PC
Diffuser Material	PC
Shape	Rectangular

Width	77mm
Height	66mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	14W/18W/22W/25W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	350mA
Light Source	LED built in
LED Type	SMD
Gear	

600mm

Length

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-6500K
Lumen Output	2500@25lm
Light Efficiency	100lm/W
CRI	80
Illumination Diagram	

Packing Info

Pcs/Carton	15
Barcode	5291889082934
HS Code	9405114090

Certification & Warranty

Warranty	3 years

switch to one light!

