



Product Datasheet

www.1-light.eu

New 2025 Edition 3>Industrial & Floodlights

38150N/V



48W CCT and Power variable linear fitting for surface installation.

Complete with power variable driver

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	New 2025 Edition 3
Family	Industrial & Floodlights
Order Code	38150N/V
Colour	Grey
Material	PC
Diffuser Material	PC
Shape	Rectangular
Length	1500mm
Width	70mm
Height	60mm
Surface Ceiling	Yes
Surface Wall	Yes



Suspended Ceiling
Indoor
Outdoor
Adjustable
IK Rating

Yes
Yes
Yes
No
8

Electrical Characteristics

Gear
Fitting + Driver
Input Voltage
50 Hz
60 Hz
Safety Class
Power(Watts)
IP Rating
Light Source
F Mark

Built In
220-240V
Yes
Yes

27W-35W-40W-48W
IP65
LED built in


Fitting
Light Source
LED Type

LED built in
SMD

Gear
Gear Type
Input Voltage
50 Hz
60 Hz
Dimmable
Protection

Led Driver
220-240V
Yes
Yes
No
0

Illumination Data

Colour Temperature	3000K-4000K-6500K
Lumen Output	5760lm (48W)
Light Efficiency	120lm/W
CRI	80
Beam Angle	120
Illumination Diagram	

Packing Info

Box Weight	1.616kg
Pcs/Carton	12
Barcode	5291889083634
HS Code	9405114090

Certification & Warranty

Warranty	3 years
----------	---------

switch to
one light!

