New 2025 Edition 2>Office & Kitchen

38161A/W/V

CCT and Power variable 50W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with power variable driver.

Complies with standard EN60598-1 and any other specific standards

IP20 · CCT V · PV · 90 CRI · UGR19 · CE

Downloads

IES · CE

Dimensions

1500mm · 75mm · 75mm

Gallery

Accessories

050170

Physical Specification

Item Group	New 2025 Edition 2
Family	Office & Kitchen
Order Code	38161A/W/V
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1500mm
Width	75mm
Height	75mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	30W-40W-50W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	▽F

Fitting

Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in
LED Type	SMD

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
IP Rating	IP20
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	4250lm (50W)
Light Efficiency	85lm/W
CRI	90
Illumination Diagram	
UGR	19

Packing Info

Pcs/Carton	9
Barcode	5291889082620
HS Code	9405413990

Certification & Warranty

one
LIGHT

switch to
one light!

one
LIGHT