

21 Industrial & Floodlights>The Supermarket LED Linear Range Aluminium

38280/W/C



80W adjustable supermarket linear light.

Complete with 2 Fixing clips, 2 Connectors & 2 Suspension kits.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Supermarket LED Linear Range Aluminium
Order Code	38280/W/C
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1200mm

Width	140mm
Height	50mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	80W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	600mA+1500mA
Safety Class	
Power(Watts)	80W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030/2835
LED Brand	Epistar

LED Number

168

Gear

Gear Type

Led Driver

Input Voltage

220-240V

Power(Watts)

16,8-22,8W & 42-60W

Power Factor

0,95

Constant Current

Yes

600mA

28-38V

1500mA

28-40V

IP Rating

IP20

Brand

BOKE

Protection

0

Illumination Data

Colour Temperature

4000K

Lumen Output

7400lm

Light Efficiency

92,5lm/W

CRI

90

Illumination Diagram



Packing Info

Box Weight

5.075kg

Pcs/Carton

4

Barcode

5291889072911

HS Code

9405413990

Certification & Warranty

switch to
one light!

one
LIGHT

