



New 2025 Edition 3>Downlights Fixed

50140F/V



36W CCT Variable 60x60 recessed frame light LED panel for T-rail false ceiling.

Complete with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

|                    |
|--------------------|
| Item Group         |
| Family             |
| Order Code         |
| Material           |
| Diffuser Material  |
| Shape              |
| Length             |
| Width              |
| Height             |
| Recessed T-Ceiling |
| Depth Required     |
| Indoor             |

|                    |
|--------------------|
| New 2025 Edition 3 |
| Downlights Fixed   |
| 50140F/V           |
| Aluminium          |
| PC                 |
| Rectangular        |
| 595mm              |
| 595mm              |
| 15mm               |
| Yes                |
| 50mm               |
| Yes                |

Adjustable

No

Electrical Characteristics

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

36W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Light Source

LED built in

LED Type

SMD

Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Output

950mA

Dimmable

No

Illumination Data

|                      |
|----------------------|
| Colour Temperature   |
| Lumen Output         |
| Light Efficiency     |
| CRI                  |
| Illumination Diagram |

3000K-4000K-5500K

3600lm

100lm/W

90



Packing Info

|            |
|------------|
| Box Weight |
| Pcs/Carton |
| Barcode    |
| HS Code    |

0.780kg

4

5291889083115

9405119090

Certification & Warranty

|                |
|----------------|
| Warranty       |
| Weee Directive |

2 years

Yes

switch to  
one light!

one  
LIGHT

