



Product Datasheet

15 Plafo>The LED Slim Plafo Range

62022B/W/W



15W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions



Gallery




Physical Specification

| Product Type | Fitting |
|--------------|--------------------------|
| Item Group | 15 Plafo |
| Family | The LED Slim Plafo Range |
| Order Code | 62022B/W/W |
| Colour | White |
| Material | PC |
| Shape | Circular |

| Height | 70mm |
|----------------------------|------------------|
| Diameter | 330mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |
| | |
| Electrical Characteristics | |
| | |
| Gear | Built In |
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 15W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | F |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 350mA |
| Voltage | 40V |
| Power(Watts) | 14W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Epistar |
| LED Number | 180 |
| | |

| F Mark | F |
|---|--|
| | |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 10,5-16W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 350mA | 30-46V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Housing Material | Plastic |
| Output Tarminal | Connector |
| Output Terminal | |
| Output Terminal | |
| Illumination Data | |
| Illumination Data | |
| Illumination Data Colour Temperature | 3000K |
| Colour Temperature Lumen Output | 3000K 1250lm |
| Colour Temperature Lumen Output Light Efficiency | 3000K |
| Colour Temperature Lumen Output | 3000K 1250lm |
| Colour Temperature Lumen Output Light Efficiency | 3000K 1250lm |
| Colour Temperature Lumen Output Light Efficiency | 3000K 1250lm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram | 3000K 1250lm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram | 3000K 1250lm 83,33lm/W |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram Packing Info Box Length | 3000K 1250lm 83,33lm/W |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram Packing Info Box Length Box Width | 3000K 1250lm 83,33lm/W 35cm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram Packing Info Box Length Box Width Box Height | 3000K 1250lm 83,33lm/W 35cm 35cm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight | 3000K 1250lm 83,33lm/W 35cm 35cm 8cm 1,08kg |

Energy Label



Certification & Warranty

Warranty 2 Years

Wee Directive Yes

switch to one light!

