

06 Downlights Fixed LED>Surface/Recessed Panels Adjustable Cut Out Hole

62116FA/W/C



16W Downlight LED, IP20

Complete with 230mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

| | |
|----------------------|---|
| Item Group | 06 Downlights Fixed LED |
| Family | Surface/Recessed Panels Adjustable Cut Out Hole |
| Order Code | 62116FA/W/C |
| Colour | White |
| Material | Plastic |
| Shape | Rectangular |
| Length | 235mm |
| Width | 235mm |
| Height | 17mm |
| Cutout Hole Diameter | 70mm-190mm |
| Recessed Ceiling | Yes |
| Depth Required | 50mm |

Indoor Yes

Adjustable No

Electrical Characteristics

Gear Built In

Fitting + Driver

Input Voltage 100-240V

50 Hz Yes

60 Hz Yes

Safety Class 

Power(Watts) 16W

IP Rating IP20

Light Source LED built in

Dimmable No

F Mark 

Fitting

Input Type Constant Current

Input Current 230mA

Voltage 68V

Power(Watts) 15,6W

IP Rating IP20

Light Source LED built in

LED Type SMD 2835


LED Brand Epistar

Gear

Gear Type Led Driver

Input Voltage 100-240V

50 Hz Yes

| | |
|------------------|---|
| 60 Hz | Yes |
| Power(Watts) | 16W |
| Power Factor | 0,5 |
| Constant Current | Yes |
| Output | 230mA |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Output Terminal | Cable |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 4000K |
| Lumen Output | 1500lm |
| Light Efficiency | 93,75lm/W |
| CRI | 80 |
| Illumination Diagram |  |

Packing Info

| | |
|------------|---------------|
| Box Weight | 0.665kg |
| Pcs/Carton | 20 |
| Barcode | 5291889067771 |
| HS Code | 9405114090 |

Certification & Warranty

switch to
one light!

one
LIGHT

