

Product Datasheet

www.1-light.eu

06 Downlights Fixed LED>Surface/Recessed Panels Adjustable Cut Out Hole 62116FA/W/W



16W Downlight LED, IP20

Complete with 230mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	I 235x235mm I

Physical Specification

Item Group	06 Downlights Fixed LED
Family	Surface/Recessed Panels Adjustable Cut Out Hole
Order Code	62116FA/W/W
Colour	White
Material	Plastic
Shape	Rectangular
Length	235mm

Width	235mm
Height	17mm
Cutout Hole Diameter	70mm-190mm
Recessed Ceiling	Yes
Depth Required	50mm



Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	230mA
Voltage	68V
Power(Watts)	15,6W
IP Rating	IP20
Light Source	LED built in

LED Type

Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes



60 Hz	Yes
Power(Watts)	16W
Power Factor	0,5
Constant Current	Yes
Output	230mA
IP Rating	IP20
Safety Class	
Dimmable	No
Output Terminal	Cable

Illumination Data

Colour Temperature	3000K
Lumen Output	1500lm
Light Efficiency	93,75lm/W
CRI	80
Illumination Diagram	

Packing InfoBox Weight0.665kgPcs/Carton20Barcode5291889067788HS Code9405114090



Warranty

switch to one light!



