



Product Datasheet

discontinue>discontinueitems

62130L/BBS/W



30W LED Decorative Plafo, IP20, suitable for residential and commercial application.

Complete with 750mA driver.

Complies with standard EN60598-1 and any other specific standards.





Downloads










Dimensions



Gallery



Physical Specification

Item Group	discontinue
Family	discontinueitems
Order Code	62130L/BBS/W
Colour	Brushed Brass
Material	Aluminium
Shape	Circular
Height	57mm

Diameter	375mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	750mA
Voltage	38V
Power(Watts)	28,5W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Bridgelux
F Mark	F
Gear	

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	20,25-30W
Power Factor	0,9
Constant Current	Yes
750mA	27-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Output Terminal	Cable
Brand	KEGU
umination Data	
umination Data	
	3000K
umination Data	
umination Data Colour Temperature	3000K
umination Data Colour Temperature Lumen Output	3000K 2550lm
Colour Temperature Lumen Output Light Efficiency	3000K 2550lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3000K 2550lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3000K 2550lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	3000K 2550lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	3000K 2550lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	3000K 2550lm 85lm/W
Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram acking Info Box Weight	3000K 2550lm 85lm/VV 80 2.500kg

Certification & Warranty

switch to one light!

