




14 Plafo>UGR19 Backlit CCT V

62140BFU/B/V



15x120cm adjustable CCT surface mounted backlit LED panel with microprismatic diffuser.

Uniform lighting, ideal for commercial applications.

Complete with 800mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions




Physical Specification

Item Group
Family
Order Code
Colour
Material
Shape
Length
Width
Height
Surface Ceiling
Indoor
Adjustable


14 Plafo
UGR19 Backlit CCT V
62140BFU/B/V
Black
Aluminium + Steel
Rectangular
1200mm
150mm
42mm
Yes
Yes
No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	800mA
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-5700K
Lumen Output	2700lm-3000lm-2850lm
Light Efficiency	90lm/W - 100lm/W - 95Lm/W
CRI	80
Illumination Diagram	
UGR	19

Packing Info

Box Weight	2.125kg
Pcs/Carton	4
Barcode	5291889077305
HS Code	9405413990

Certification & Warranty

Warranty	3 years
Weee Directive	Yes

switch to
one light!

