

## **Product** Datasheet

#### 18 Decorative>The Cloud Series

### 62148D/W



108W LED Cloud Plafo , IP20 suitable for residential and commercial application .

Complete with 1300mA drivers.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	910mm

#### **Physical Specification**

Item Group	18 Decorative
Family	The Cloud Series
Order Code	62148D/W
Colour	White
Material	Metal
Diffuser Material	PC
Shape	Circular

Diameter	910mm
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No



Fitting + Driver         Input Voltage       220-240V         50 Hz       Yes         60 Hz       Yes         Safety Class       Omega         Power(Watts)       108W         IP Rating       IP20         Light Source       LED built in         Dimmable       No         F Mark       F	Gear	Built In
Input Voltage       220-240V         50 Hz       Yes         60 Hz       Yes         Safety Class       Yes         Power(Watts)       108W         IP Rating       IP20         Light Source       LED built in         Dimmable       No		
50 HzYes60 HzYesSafety ClassImage: ClassPower(Watts)108WIP RatingIP20Light SourceLED built inDimmableNo	Fitting + Driver	
60 Hz     Yes       Safety Class     Image: Class       Power(Watts)     108W       IP Rating     IP20       Light Source     LED built in       Dimmable     No	Input Voltage	220-240V
Safety ClassImage: Class clas	50 Hz	Yes
Power(Watts)     108W       IP Rating     IP20       Light Source     LED built in       Dimmable     No	60 Hz	Yes
IP Rating       IP20         Light Source       LED built in         Dimmable       No	Safety Class	
Light Source       LED built in         Dimmable       No	Power(Watts)	108W
Dimmable No	IP Rating	IP20
	Light Source	LED built in
F Mark	Dimmable	No
	F Mark	F

Fitting

Input Type	Constant Current
Input Current	1300mA
Voltage	2x40V
Power(Watts)	2x52W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	F

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	35-55W




Power Factor	0,9
Constant Current	Yes
1300mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud

#### Illumination Data

Colour Temperature	3000K
Lumen Output	8700lm
Light Efficiency	80,55lm/W
CRI	80
Illumination Diagram	

# Packing Info Pcs/Carton 1 Barcode 5291889062905 HS Code 9405409900

#### Energy Label





Warranty	3 Years
Weee Directive	Yes

## switch to one light!

Certification & Warranty



