



Product Datasheet

21 Industrial & Floodlights>The Industrial IP65 UFO Range Power Adjustable

63200N/V

& CCT Variable



CCT Variable and power adjustable 120W/160W/200W SMD LED Industrial High Bay, IP65.

Supplied with 3-step dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.













Downloads










Dimensions



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 UFO Range Power Adjustable & CCT Variable
Order Code	63200N/V
Colour	Black
Material	Aluminium
Diffuser Material	PC
Shape	Circular
Height	177mm
Diameter	350mm
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	120W/160W/200W
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	3-Step Dimming
Cable Length	150cm
F Mark	F
Fitting	
Input Type	Constant Current
Light Source	LED built in
LED Type	SMD 2835
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power Factor	0,9
Constant Current	Yes

Colour Temperature 4000K-4700K-5700K Lumen Output 30000lm (200W) Light Efficiency 150lm/W CRI 80 Beam Angle 90° Illumination Diagram Illumination Diagram

Packing Info	
Pcs/Carton	1
Barcode	5291889078364
HS Code	9405413990

Certification & Warranty	
Warranty	5 years
Weee Directive	Yes



Illumination Data

