



21 Industrial & Floodlights>The Industrial IP65 UFO Range DALI

63240NL/C



240W SMD LED DALI Industrial High Bay, IP65.

Supplied with DALI 2 driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions





Physical Specification


Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 UFO Range DALI
Order Code	63240NL/C
Colour	Black
Material	Aluminium
Diffuser Material	PC
Shape	Circular
Height	184mm
Diameter	400mm
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes


Adjustable	No
------------	----

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	240W
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	Dali
Cable Length	150cm
F Mark	

Fitting	
Input Type	Constant Current
Light Source	LED built in
LED Type	SMD 2835

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power Factor	0,9
Constant Current	Yes
Safety Class	

Brand	Lifud
Illumination Data	
Colour Temperature	4000K
Lumen Output	36000lm
Light Efficiency	150lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info	
Box Weight	5.000kg
Pcs/Carton	1
Barcode	5291889078388
HS Code	9405413990

Certification & Warranty	
Warranty	5 years
Weee Directive	Yes

switch to  
one light!

