


Product Datasheet

www.1-light.eu

09 Track Lights>The COB Track Light Range Aluminium

65614NT/B/W



42W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items



40001A/B



40002A/B



40003A/B

Physical Specification

Item Group	09 Track Lights
Family	The COB Track Light Range Aluminium
Order Code	65614NT/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	128mm

Diameter	100mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	42W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1050mA
Voltage	38V
Safety Class	<u> </u>
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Sanan
Gear	

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	35-42W
Power Factor	0,9
Constant Current	Yes
1050mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Protection	Short Circuit Protection
Ilumination Data	
	200014
Colour Temperature	3000K
Colour Temperature Lumen Output	3780lm
Colour Temperature Lumen Output Light Efficiency	3780lm 90lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3780lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3780lm 90lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3780lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3780lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3780lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3780lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3780lm 90lm/VV 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3780lm 90lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	3780lm 90lm/W 90 38° 25cm 15cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	3780lm 90lm/W 90 38° 25cm 15cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	3780lm 90lm/W 90 38° 25cm 15cm 10,5cm 1.510kg

Certification & Warranty

Warranty 3 years

switch to one light!

