



Product Datasheet

09 Track Lights>The Black Heatsink Range

65628T/W/W



15W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40003A/W

Physical Specification

Item Group	09 Track Lights
Family	The Black Heatsink Range
Order Code	65628T/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	132mm

Diameter	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	400mA
Voltage	35V
Power(Watts)	14W

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	400mA
Voltage	35V
Power(Watts)	14W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V

IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
one	

50 Hz	Yes
60 Hz	Yes
Power(Watts)	12-18W
Power Factor	0,9
Constant Current	Yes
400mA	30-45V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
Protection	Short Circuit Protection
Illumination Data	
Illumination Data Colour Temperature	3000K
	3000K 1095lm
Colour Temperature	
Colour Temperature Lumen Output	1095lm
Colour Temperature Lumen Output Light Efficiency	1095lm 73lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1095lm 73lm/VV 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1095lm 73lm/VV 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1095lm 73lm/VV 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1095lm 73lm/W 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	1095lm 73lm/W 80 45° 20cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	1095lm 73lm/W 80 45° 20cm 11,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	1095lm 73lm/W 80 45° 20cm 11,5cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height Box Weight	1095lm 73lm/W 80 45° 20cm 11,5cm 10cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	1095lm 73lm/W 80 45° 20cm 11,5cm

Barcode	5291889043904
HS Code	9405409900

Certification & Warranty		
Warranty	2 Years	
Average Lifetime	30000hours	
Weee Directive	Yes	



