

www.1-light.eu

09 Track Lights>The COB Cylinder Track Light

65642AT/B/W



10W track spot with COB LED, ideal for shops and showrooms.

Supplied with electronic high frequency control driver as standard.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Related items







40002A/B



40003A/B

Physical Specification

Item Group	09 Track Lights
Family	The COB Cylinder Track Light
Order Code	65642AT/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	147mm

Diameter	55mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	38V
Safety Class	ŢIII>
Power(Watts)	9,5W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Sanan
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-10W
Power Factor	0,9
Constant Current	Yes
250mA	25-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Lifud
Protection	Short Circuit Protection
	3000K
lumination Data	
lumination Data Colour Temperature	3000K
Colour Temperature Lumen Output	3000K 900lm
Colour Temperature Lumen Output Light Efficiency	3000K 900lm 90lm/W
Colour Temperature Lumen Output Light Efficiency CRI	3000K 900lm 90lm/VV
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 900lm 90lm/VV
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	3000K 900lm 90lm/VV
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 900lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 900lm 90lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 900lm 90lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	3000K 900lm 90lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram acking Info Box Length Box Width	3000K 900lm 90lm/VV 90 38° 22cm 8,5cm

Pcs/Carton	24
Barcode	5291889053880
HS Code	9405413990

Certification & Warranty Warranty 5 years

Weee Directive Yes



