

Product Datasheet

14 Plafo>The LED Plafo Outdoor Round

67280N/W/C



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads	Dimensions
	260mm 75mm
Physical Specification	

Item Group	14 Plafo
Family	The LED Plafo Outdoor Round
Order Code	67280N/W/C
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular

Height	75mm
Diameter	260mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes



Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in

LED Type

SMD 2835

LED Brand	Epistar
LED Number	81
F Mark	F
Gear	
Gear Type	Led Driver



Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-16W
Power Factor	0,9
Constant Current	Yes
500mA	19-32V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise

Illumination Data

Colour Temperature	4000K
Lumen Output	960lm
Light Efficiency	60lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	27cm
Box Width	27cm
Box Height	8cm

Box Weight	0.980kg
Pcs/Carton	10
Barcode	5291889043294
HS Code	9405114090



Warranty	2 Years
Weee Directive	Yes

switch to one light!

Certification & Warranty



