



Product Datasheet

19 Wall Recessed & Inground>Outdoor Dark Light Wall Recessed Die cast

68064/AN/W



3,6W LED wall recessed light, IP65, ideal for both indoor and outdoor installation.

Complete with 350mA driver.

Supplied with box for concrete installation

Complies with standard EN60598-1 and any other specific standards.













Downloads










Dimensions



Physical Specification

Item Group	19 Wall Recessed & Inground
Family	Outdoor Dark Light Wall Recessed Die cast
Order Code	68064/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	65mm
Width	107mm
Height	65mm
Cutout Hole Width	97mm
Cutout Hole Length	62mm
Recessed wall	Yes

Depth Required Indoor Outdoor	65mm Yes Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In

Fitting + Driver Input Voltage 100-240V 50 Hz Yes Yes 60 Hz Safety Class Power(Watts) 3,6W IP Rating IP65 Light Source LED built in Dimmable No F F Mark Fitting Input Type **Constant Current** Input Current 350mA 9V Voltage Safety Class Power(Watts) 3W IP Rating IP65 Light Source LED built in LED Type SMD LED Brand Philips LED Number 6

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	1-4VV
Power Factor	0,5
Constant Current	Yes
350mA	3-10V
IP Rating	IP20
Safety Class	
Brand	Eaglerise
Protection	0
Illumination Data	
Colour Temperature	3000K
	3000K 85lm
Colour Temperature	
Colour Temperature Lumen Output	85lm
Colour Temperature Lumen Output Light Efficiency	85lm 23,61lm/W
Colour Temperature Lumen Output Light Efficiency CRI	85lm 23,61lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	85lm 23,61lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	85lm 23,61lm/W 80 44°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	85lm 23,61lm/W 80 44°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	85lm 23,61lm/W 80 44° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	85lm 23,61lm/W 80 44°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	85lm 23,61lm/W 80 44° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	85lm 23,61lm/W 80 44° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length Box Width	85lm 23,61lm/W 80 44° Yes 13cm 10cm

Pcs/Carton	24
Barcode	5291889057475
HS Code	9405413990

Certification & Warranty

Warranty 2 years



