



21 Industrial & Floodlights>The LED Park Light Die cast

70112/B/W



LED outdoor light for poles 3m and higher. Ideal for parks, parkings, playgrounds.Post Diamerter 60mm.

Complete with 2400mA driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery





Physical Specification

Item Group	21 Industrial & Floodlights
Family	The LED Park Light Die cast
Order Code	70112/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	530mm

Diameter	450mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8


Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	75W
IP Rating	IP66
Light Source	LED built in
Dimmable	No
Cable Length	150cm
F Mark	

Fitting	
Input Type	Constant Current
Input Current	2400mA
Voltage	30V
Power(Watts)	72W
IP Rating	IP66
Light Source	LED built in
LED Brand	Seoul

Gear

Gear Type
Input Voltage
50 Hz
60 Hz
Power(Watts)
Power Factor
Constant Current
Output
Voltage Range
IP Rating
Safety Class
Dimmable
Housing Material
Output Terminal
Brand

Led Driver
100-240V
Yes
Yes
52,8-134,4W
0,9
Yes
2400mA
22-56V
IP20

No
Plastic
Connector
Sosen

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram

3000K
9000lm
120lm/W
80


Packing Info

Box Weight
Pcs/Carton
Barcode
HS Code

9.300kg
1
5291889075462
9405413990

Certification & Warranty

Warranty

5 years

Weee Directive

Yes

switch to
one light!

one
LIGHT

