



Product Datasheet

20 Industrial & Floodlights>CCT V Streetlight

70118A/AN/V



50W CCT Variable DOB LED street light.

Driver on board.

Accessory 050400A/AN for wall mounting or 050400B/AN for post top diameter 60mm or side-entry diameter 60mm must be ordered separately.

Complies with standard EN60598-1 and any other specific standards.














Downloads







Dimensions



Gallery





Must be ordered separately





one

Physical Specification 20 Industrial & Floodlights Item Group CCT V Streetlight Family Order Code 70118A/AN/V Colour Anthracite Aluminium Material PC Diffuser Material Shape Rectangular 330mm Length Width 145mm Height 60mm Outdoor Yes Adjustable 1 Direction **IK Rating** 8 **Electrical Characteristics** Gear No Fitting + Driver Input Voltage 220-240V 50 Hz Yes 60 Hz Yes Safety Class Power(Watts) 50W IP Rating IP65 Light Source LED built in

Illumination Data

Dimmable

Cable Length

No

100cm

Colour Temperature	3000K-4000K-5000K
Lumen Output	5000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	130°x75°
Illumination Diagram	

Packing Info

Certification & Warranty Warranty Weee Directive Yes

switch to one light!

