



New 2025 Edition 3>Industrial & Floodlights

7028CE/B/V



150W DOB LED CCT Variable floodlight with adjustable mounting bracket.

IP65 rated for outdoor use.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	New 2025 Edition 3
Family	Industrial & Floodlights
Order Code	7028CE/B/V
Colour	Black
Material	Aluminium
Diffuser Material	Glass
Shape	Rectangular
Length	327mm
Width	273mm
Height	30mm
Surface Ceiling	Yes
Surface Wall	Yes

Surface Floor/Ground
Outdoor
Adjustable
IK Rating

Yes
Yes
1 Direction
6

Electrical Characteristics

Gear
Fitting + Driver
Input Voltage
50 Hz
60 Hz
Safety Class
Power(Watts)
IP Rating
Light Source
Dimmable
F Mark

Built In
220-240V
Yes
Yes

150W
IP65
LED built in
No


Fitting
Light Source
LED Type
Cable Length

LED built in
SMD
50cm

Gear
Gear Type
Input Voltage
Dimmable

Led Driver
220-240V
No

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Beam Angle
Illumination Diagram

3000K-4000K-6500K

15000lm

100lm/W

80

110°



Packing Info

Certification & Warranty

Warranty
Average Lifetime
Weee Directive

2 Years

36000Hrs L70B50

Yes

switch to
one light!

one
LIGHT

