



New 2025 Edition 3>Strips & Profiles

7820C/RGBW



19W/meter RGBW Digital SPI flexible LED light strip, with 60 SMD5050 LEDs/meter.

Supplied in 10 meters roll with receiver, remote control and 3M double-face adhesive tape.

Includes 40 selectable program modes.

Can be cut every 10cm (6-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	New 2025 Edition 3
Family	Strips & Profiles
Order Code	7820C/RGBW
Shape	Rectangular
Length	10000mm
Width	10mm
Height	2mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes





Indoor

Yes

Electrical Characteristics

Fitting

Input Type
Input Voltage
Safety Class
Power(Watts)
IP Rating
Light Source
LED Type
F Mark

Constant Voltage
24V DC

19W/m
IP20
LED built in
SMD 5050


Illumination Data

Colour Temperature
Lumen Output
CRI
Illumination Diagram

RGB+3000K
292lm/m (3000K)
80


Packing Info

Box Weight
Pcs/Carton
Barcode
HS Code

0.576kg
25
5291889084143
9405499090

Certification & Warranty

switch to  
**one light!**

