

# **Product Datasheet**

www.1-light.eu

08 Strips & Profiles>The 19,2W/m Indoor 24V

7825/C



Flexible LED light strip, with SMD2835 LEDs, 140LEDs/meter, 19,2W/meter.Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing.

Can be cut every 5cm (7-LED segment).

Requires 24V DC constant voltage LED driver.

Complies with standard EN60598-1 and any other specific standards.



### Downloads









### Dimensions

Cut every 5cm (7-LED segment)



### Gallery



### Accessories





one

Physical Specification	
Item Group	08 Strips & Profiles
Family	The 19,2W/m Indoor 24V
Order Code	7825/C
Shape	Rectangular
Length	5000mm
Width	10mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Electrical Characteristics	
Fitting	
Input Type	Constant Voltage
Input Voltage	24V DC
Safety Class	

19,2W/m

LED built in

SMD 2835

140LEDs/m

Refond

F

IP20

Colour Temperature	4000K
Lumen Output	1728lm/m
Light Efficiency	90lm/W

Power(Watts)

IP Rating

Light Source

LED Type

LED Brand

LED Number

F Mark


Illumination Data

CRI	90
Illumination Diagram	

Packing Info	
Box Length	24cm
Box Width	21,5cm
Box Height	2cm
Box Weight	0.212kg
Pcs/Carton	40
Barcode	5291889046004
HS Code	9405499090

F

# Energy Label



Energy Class

## Certification & Warranty

Warranty 5 years

# switch to one light!

