

Product Datasheet

www.1-light.eu

08 Strips & Profiles>The 230V IP65 Range

7860/W



230V Waterproof LED strip 9W/m, IP65.

Supplied in 50m rolls.

Can be cut every 1m.

Requires power supply order code 7860P.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions



Gallery



Must be ordered separately



7860P

Accessories











7860C

7860F


7860L

7860R

T hysical openication	
Item Group	08 Strips & Profiles
Family	The 230V IP65 Range
Order Code	7860/W
Shape	Rectangular
Length	50000mm
Width	16mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	9W/m
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	F
Fitting	
Safety Class	
Safety Class Power(Watts)	9W/m

IP Rating	IP65
Light Source	LED built in
LED Type	SMD 3528
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	450W
Power Factor	0,9
IP Rating	IP65
Safety Class	
Brand	0
Protection	0
Protection	
Protection Ilumination Data	0
Protection	
Protection Ilumination Data	0
Protection Ilumination Data Colour Temperature	0 3000K
Protection Ilumination Data Colour Temperature Lumen Output	0 3000K 750lm
Protection Illumination Data Colour Temperature Lumen Output Light Efficiency	0 3000K 750lm 95,55lm/W
Protection Illumination Data Colour Temperature Lumen Output Light Efficiency CRI	0 3000K 750lm 95,55lm/W
Protection Illumination Data Colour Temperature Lumen Output Light Efficiency CRI	0 3000K 750lm 95,55lm/W
Protection Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	0 3000K 750lm 95,55lm/W
Protection Illumination Data Colour Temperature Lumen Output Light Efficiency CRI Illumination Diagram	3000K 750lm 95,55lm/W 80
Protection Illumination Data	0 3000K 750lm 95,55lm/W 80 0.152kg
Protection Illumination Data	0 3000K 750lm 95,55lm/W 80 0.152kg 50

Energy Label



Energy Class F

Certification & Warranty

Warranty 2 years

Weee Directive

switch to one light!



Yes